

# Coil Winder TD3T

*The Model TD6-4 is a quality built, single head bench winder controlled by a well-proven microprocessor unit with a memory capacity capable of storing 1000 programmes.*

Each programme controls:

- Start position
- Winding width and wire diameter
- Number of turns
- Acceleration and deceleration
- Winding speed and direction
- All machines are equipped with a fail-safe brake and polycarbonate guard

Variations in mechanical specifications are offered; for example:

- With or without traverse
- With or without tailstock
- Low speed, high torque gear motor
- More powerful drive motor
- Large pitch facility
- Multiple wire guides
- Long machine bed to customer's requirements
- Foil/strip support table option
- Tooling to suit customer's specifications



## TECHNICAL SPECIFICATIONS

**Wire Pitching:** 0.001mm - 9.999mm  
**Coil Diameter:** 200mm maximum  
**Winding Length:** 150mm- optional 250mm  
**Spindle Speed:** Variable up to 10,000 rpm  
**Supply:** 240V 50 Cycles 10 Amp  
**Motor:** 0.44 kW



Unit 5, Bawdon Lodge Farm, Charley Rd. Nanpantan, Leicestershire, LE12 9YE  
 Phone: +44 (0) 1509 239 832 • Fax: +44 (0) 1509 239 837  
 e-mail: sales@td-engineering.com  
 web: td-engineering.com

OR  
CONTACT:

**WYREPAK** INDUSTRIES  
 wyrepakdave@yahoo.com  
 USA phone: 860-632-5477